

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)

2. REPORT TYPE
Technical Papers

3. DATES COVERED (From - To)

4. TITLE AND SUBTITLE

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)

5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

8. PERFORMING ORGANIZATION
REPORT

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

10. SPONSOR/MONITOR'S
ACRONYM(S)

11. SPONSOR/MONITOR'S
NUMBER(S)

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

20020823 058

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:

a. REPORT

b. ABSTRACT

c. THIS PAGE

Unclassified

Unclassified

Unclassified

17. LIMITATION
OF ABSTRACT

A

18. NUMBER
OF PAGES

19a. NAME OF RESPONSIBLE
PERSON

Leilani Richardson

19b. TELEPHONE NUMBER
(include area code)
(661) 275-5015

41 items enclosed



Sea Water Immersion of GEM II Propellant

C. I. Merrill and J. D. O'Drobinak

AFRL

Edwards AFB, CA

TP-1998-076

PAR 120084

MEMORANDUM FOR IN-HOUSE PUBLICATIONS

14 Apr 98

FROM: PROI (TI) (STINFO)

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-TP-1998-076

C.I. Merrill and J.D. O'Drobinak "Sea Water Immersion of GEM II Propellant"
VuGraphs
(Statement A)




Pacific Seawater Aging of GEM Propellant

A1008.



Cutting Into Blister Doesn't Cause Deflation

Pacific Seawater Aging of GEM Propellant




Casting Void Below Blister, Blister Is Solid




Pacific Seawater Aging of GEM Propellant



Clear Binder Blister




Building in which the aging study is being conducted.




Swimming pool inside the building showing the cover tarp partially removed.
String hanging over the sides of the pool are connected to baskets
containing propellant samples.




Circulation pump together with hoses connected to swimming pool.



Two baskets containing propellant samples on bottom of pool. Basket on the left contains samples buried in the sand.




2" Cube / Wet




2" Cube / Dry

Representative appearance of wet and dry samples that were aged in the swimming pool.



Drop Weight Impact Tester.

RELATIVE SWELLING RATES OF WET AGED GEM PROPELLANT



EFFECT OF AGING TIME AND SAMPLE SIZE ON FIRE TEST RESULTS

Test	Sample	Aging Water	Cube/State	Soak Time ^a	Time to Burn ^b
1	Control	None	1"/Dry	0.00	0
2	5-5i	S ^c	1"/Wet	1.11	60
3	7	S	1"/Dry	1.11	0
7	2-1i	S	1"/Dry	2.97	0
8	1-1o	S	1"/Wet	2.97	125
15	1-1i	S	1"/Dry	5.12	0
16	3-1i	S	1"/Wet	5.12	225
11	6t	S	2"/Dry	2.08	0
12	3	S	2"/Wet	2.08	90
17	2c	S	2"/Dry	5.12	0
18	1	S	2"/Wet	5.12	>300 ^f
25	2t	S	2"/Wet	5.12	200
26	5	S	2"/Dry	8.69	0
27	0	S	2"/Wet	8.69	270
4	3	C ^d	1"/Wet	1.11	55
5	0	C	1"/Dry	2.97	0
6	5	C	1"/Wet	2.97	115
9	3cc	P ^e	1"/Wet	2.00	225
10	3cd	P	1"/Dry	2.00	0
19	2c-2io	P	1"/Dry	3.43	0
20	3c-1ii	P	1"/Wet	3.43	140
28	4cd	P	1"/Dry	6.97	0
29	5 3(90)	P	1"/Wet	6.97	425
32	2t-3iidd	P	1"/Dry	9.97	0
33	0	P	1"/Wet	9.97	348 ^g
13	6t	P	2"/Dry	2.00	0
14	6c	P	2"/Wet	2.00	60
21	3cc-1i	P	2"/Dry	4.00	0
22	2c-2io	P	2"/Wet	4.00	120
30	2c	P	2"/Dry	8.00	0
31	0-2c	P	2"/Wet	8.00	352
34	3cc-200	P	2"/Dry	9.97	0
35	4ccc-1op	P	2"/Wet	9.97	354
23	3tt	P	4"/Dry	4.00	0
24	6t	P	4"/Wet	4.00	120

a. Time in weeks

b. Approximate time in seconds

c. Simulated seawater

d. Cape Canaveral water

e. Pacific seawater

f. Sample did not burn before fuel flame expired.

g. Fire intensity was greater than that of Test 29.

FRICTION & IMPACT TEST RESULTS OF AGED GEM PROPELLANT

Sample	Cube Size	Aging Time ^a	No Fires	Location/State	Impact, kg-cm	Frict., E, kg-cm
Reference ^b	-	0.00	4 (7)	Dry	93	12.0
0-7	1"	2.00	5 (5)	Skin/Dry	102	9.6
2c-1i	1"	2.00	5 (5)	Skin/Wet	250 ^c	28.8
"	1"	2.00	5 (5)	Center/Wet	132	14.4
3c-2io	1"	3.43	5 (5)	Skin/Dry	108	16.8
3c-3iio	1"	3.43	5 (5)	Skin/Wet	250 ^c	36.0 ^d
"	1"	3.43	3 (5)	Center/Wet	240	21.6
6c	1"	6.97	4 (5)	Skin/Dry	99	14.4
"	1"	6.97	3 (5)	Centre/Dry	96	-
4ccc	1"	6.97	5 (5)	Skin/Wet	250 ^c	36.0 ^d
"	1"	6.97	5 (5)	Center/Wet	141	21.6
2t	1"	9.97	3 (5)	Skin/Dry	96	14.4
"	1"	9.97	4 (5)	Center/Dry	99	-
3c-3ioo	1"	9.97	5 (5)	Skin/Wet	250 ^c	36.0 ^d
"	1"	9.97	5 (7)	Center/Wet	138	28.8
8	2"	2.00	5 (5)	Skin/Wet	250 ^c	32.4
"	2"	2.00	4 (5)	Center/Wet	108	14.4
0-5cccd	2"	4.00	5 (5)	Skin/Wet	250 ^c	36.0 ^d
"	2"	4.00	4 (5)	Center/Wet	105	14.4
1	2"	8.00	5 (5)	Skin/Wet	250 ^c	32.4
"	2"	8.00	4 (5)	Center/Wet	105	14.4
3cc-2ii	2"	9.97	5 (5)	Skin/Wet	250 ^c	36.0 ^d
"	2"	9.97	4 (5)	Center/Wet	114	14.4


a. Aging time in weeks

b. Propellant was not aged.


c. 250 kg-cm impact value is upper limit for test.

d. 36.0 kg-cm friction values is upper limit for test.

AP DEPLETION RATES FOR PROPELLANT AGED IN SEA WATER



AP DEPLETION FOR PROPELLANT AGED IN PACIFIC SEA WATER



GEM II PROPELLANT IN SEA WATER CONCLUSIONS

**AP DEPLETION IN SEA WATER GIVES STRAIGHT LINE IN LOGARITHMIC
PLOT**

**WET, THEN DRIED PROPELLANT IS NOT MORE FRICTION OR IMPACT
SENSITIVE**

WET PROPELLANT IS VERY INSENSITIVE TO FRICTION AND IMPACT

**BURNING OF LONG TERM WATER SOAKED PROPELLANT EXHIBITED ONLY
SLOWER AND SLOWER FIRE INITIATION.**

NO EXPLOSIONS OR FIRE BRAND THROWING WERE OBSERVED